

Braided hose

## FITCOFLEX-I-S55PET®

Mechanical braided hose with excellent protection from noise, self-extinguishing and a high operating temperature.

### Application:

Bundeling and protection of cable harness especially in car motor compartment and vehicle interior because of its noise reducing effect.

### Operating temperature:

-55°C bis +150°C

### Standard color:

black

| Description           | Recommended range of application [mm] |         |
|-----------------------|---------------------------------------|---------|
|                       | (Ø min)                               | (Ø max) |
| FITCOFLEX-I-S55PET 4  | 3.5                                   | 11      |
| FITCOFLEX-I-S55PET 10 | 8                                     | 20      |
| FITCOFLEX-I-S55PET 14 | 12                                    | 24      |
| FITCOFLEX-I-S55PET 18 | 16                                    | 28      |
| FITCOFLEX-I-S55PET 22 | 20                                    | 30      |
| FITCOFLEX-I-S55PET 26 | 24                                    | 34      |
| FITCOFLEX-I-S55PET 30 | 25                                    | 35      |

Special sizes on request

### Properties:

- Excellent noise protection
- Low weight, high flexibility, high mechanical protection
- High expansion
- Very good media resistance
- Self-extinguishing (DIN 75200 / FMVSS 302)
- 100% recycleable