

PTFE heat shrink tubing with melting FEP core

FITCOTUBE® TF/FP-A

Double-walled, high temperature resistant heat shrinkable tubing made of PTFE with melting FEP core for sealing and encapsulation of components with highest demands on temperature resistance and/or chemical resistance against very aggressive substances.

- Operating temperature:** -100°C to +200°C
- Shrining temperature:** Ca. 330°C
- Shrink ratio:** Ca. 1,5:1
- Standard color:** Nature / transparent (milky)



Description	Inner diameter (mm)		Wall thickness (mm)
	as supplied (min.)	after full recovery (max.)	after full recovery (nom.)
TF/FP-036A-S	0,91	0,00	0,60
TF/FP-060A-S	1,52	0,00	0,70
TF/FP-130A-S	3,30	0,00	0,80
TF/FP-160A-S	4,05	0,00	0,80
TF/FP-190A-S	4,80	1,60	0,90
TF/FP-250A-S	6,40	3,20	0,90
TF/FP-350A-S	8,90	4,80	0,90
TF/FP-450A-S	11,40	7,90	1,40
TF/FP-700A-S	17,80	11,20	1,40
TF/FP-950A-S	24,10	16,00	1,65
-thin walled-			
TF/FP-065A-L	1,65	0,00	0,38
TF/FP-115A-L	2,90	1,15	0,38
TF/FP-130A-L	3,30	1,50	0,38
TF/FP-180A-L	4,60	1,65	0,38
TF/FP-190A-L	4,80	1,80	0,38
TF/FP-240A-L	6,10	3,80	0,50
TF/FP-350A-L	8,90	5,40	0,65
TF/FP-480A-L	12,20	8,00	0,80
TF/FP-700A-L	17,80	12,70	1,00
TF/FP-1000A-L	25,40	17,80	1,15

- Packaging:** 1.22m lengths. Special sizes on request.
- Processing note:** Care for clean and accurate cutting edges. Start shrinkage on the end. Pre-heat metal body.