

Braided hose

FITCOFLEX®-B-PA25

Protective sleeve with an open weave structure manufactured using polyamide 6.6 (PA6.6) monofilaments.

Description:

FITCOFLEX®-B-PA25 is ROHS and REACH compliant and halogen free. Manufactured using 0.25mm PA6.6 monofilaments, FITCOFLEX®-B-PA25 offers very good abrasion resistance and is particularly suited to the protection of pipes, hoses and cable harnesses. It offers outstanding protection against oil, fuel and other chemical agents. FITCOFLEX®-B-PA25 has a tough, lightweight and flexible construction.

Specification:

Meets the requirements of PSA D441959/B CAT C. Independent test reports (SGS RES 217215 02A / 02B) available upon request.

Operating temperature: - 40°C to + 125°C

Standard colour: Black
Other colours on request



| Description | Diameter (mm) | |
|---------------------|---------------|------------------|
| | Nominal Size | Maximum Diameter |
| FITCOFLEX-B-PA25 2 | 2 | 3.5 |
| FITCOFLEX-B-PA25 3 | 3 | 6.0 |
| FITCOFLEX-B-PA25 4 | 4 | 6.5 |
| FITCOFLEX-B-PA25 5 | 5 | 8.5 |
| FITCOFLEX-B-PA25 6 | 6 | 9.5 |
| FITCOFLEX-B-PA25 8 | 8 | 12.0 |
| FITCOFLEX-B-PA25 10 | 10 | 14.0 |
| FITCOFLEX-B-PA25 12 | 12 | 18.0 |
| FITCOFLEX-B-PA25 14 | 14 | 19.0 |
| FITCOFLEX-B-PA25 16 | 16 | 21.0 |
| FITCOFLEX-B-PA25 18 | 18 | 25.0 |
| FITCOFLEX-B-PA25 20 | 20 | 28.0 |
| FITCOFLEX-B-PA25 22 | 22 | 30.0 |
| FITCOFLEX-B-PA25 25 | 25 | 32.0 |
| FITCOFLEX-B-PA25 30 | 30 | 36.0 |
| FITCOFLEX-B-PA25 40 | 40 | 48.0 |
| FITCOFLEX-B-PA25 50 | 50 | 60.0 |
| FITCOFLEX-B-PA25 60 | 60 | 68.0 |

Special sizes on request