

Expandable Braided Sleeving

FITCOFLEX®-B- HP/HPT

Protective sleeve made of PET (polyethylene terephthalate) multifilaments braided in a tight construction.

Description:

FITCOFLEX®-B-HP and even more HPT is extremely tough and resistant to abrasion and cut through, thus extending considerably the lifetime of the protected tube or pipe.

It offers additional protection versus the standard FITCOFLEX®-B types. The braiding construction and material used in this product offers a superior abrasion grade which offers, in some critical parts, the highest protection possible.

The sleeve is manufactured in a way that through the hot cut no issues are risen for the installation.

Operating temperature:	- 70°C to + 150°C
Standard color:	Black Other colors on request
Size range:*	3mm – 50mm
Applications:	Wire harnesses Pipes and hoses Sensor assemblies



Description	Diameter (mm)	
	Nominal Size	Maximum Diameter
FITCOFLEX®-B-HP/HPT 3	3	5
FITCOFLEX®-B- HP/HPT 5	5	8
FITCOFLEX®-B- HP/HPT 10	10	14
FITCOFLEX®-B- HP/HPT 15	15	20
FITCOFLEX®-B- HP/HPT 20	20	25
FITCOFLEX®-B- HP/HPT 25	25	30
FITCOFLEX®-B- HP/HPT 30	30	35

*Other sizes on request

Packaging: On spools or cut lengths.