

**Braided Sleeve** 

## **FITCOFLEX<sup>®</sup>-J-NO**

Braided sleeve made of Nomex<sup>®</sup> fiber, self-extinguishing, non-melting, especially designed and suitable for protection of wire and cable bundles against flame, high temperatures and mechanical abrasion. Preferably used in high-tech fields such as racing, military industry, aerospace, and fire protection.

Operating temperature:

-196°C to +350°C, carbonized at 370°C

Standard color:





Description	Flat Width (mm)	Spread Range (mm)	
	min.	min.	max.
FITCOFLEX-J-NO 4	4	1	4
FITCOFLEX-J-NO 6	6	5	8
FITCOFLEX-J-NO 8	8	6	10
FITCOFLEX-J-NO 10	10	7	13
FITCOFLEX-J-NO 12	12	8	16
FITCOFLEX-J-NO 15	15	10	20
FITCOFLEX-J-NO 20	20	14	26
FITCOFLEX-J-NO 25	25	18	33
FITCOFLEX-J-NO 30	30	20	39
FITCOFLEX-J-NO 40	40	30	52
FITCOFLEX-J-NO 50	50	40	65

**Specifications/Features:** 

self-extinguishing (EN3844-1)

Resistant against acid and alkali, bleaching agents, anti-fungal and mildew, not affected by freon and gasoline

Packaging:

Continuous lengths coiled.

 GREMCO GmbH · Sterzinger Str. 6 · D-86165 Augsburg · T +49.821.272 63-0 · F +49.821.272.63-44 · info@gremco.de · www.gremco.de ·

 PDS No.: 20230315215454
 Version: UWM0323-0
 Print Date: 17. Mrz. 2023

FITCO<sup>\*</sup> = trademark of GREMCO

All of the above information is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. GREMCO make no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. GREMCO's only obligations are those in the Standard Terms and Conditions of Sale for this product, and in no case will GREMCO be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use or misuse of the product.