

Expandable Braided Sleeving

FITCOFLEX®-B-PA/2PET

Protective sleeve manufactured using PA66 (Polyamide 6.6) and PET (Polyester) monofilaments with a diameter size of 0.25mm.

FITCOFLEX®-B-PA/2PET has an open weave structure which permits drainage and prevents condensation. It is RoHS and REACH compliant and halogen free.

FITCOFLEX®-B-PA/2PET offers very good abrasion resistance in combination with high flexibility and is particularly suited to the protection of pipes, hoses and cable harnesses. It also offers outstanding protection against oil, liquids, fuel and other chemical agents.

Specifications:

Meets the requirements of PSA D441959/B CAT D. Independent test reports (SGS RES 217215 04A / 04B) available upon request.

FITCOFLEX-B-PA/2PET also meets the requirements of RENAULT D441959/B CAT C3. Independent test reports (SGS RES 217215 03) available upon request.

Operating temperature: - 40°C to + 150°C

Standard color: Black
Other colors on request



Description	Diameter (mm)	
	Nominal Size	Maximum Diameter
FITCOFLEX-B-PA/2PET 4	4	8
FITCOFLEX-B-PA/2PET 6	6	12
FITCOFLEX-B-PA/2PET 8	8	14
FITCOFLEX-B-PA/2PET 10	10	20
FITCOFLEX-B-PA/2PET 12	12	22
FITCOFLEX-B-PA/2PET 13	13	24
FITCOFLEX-B-PA/2PET 15	15	25
FITCOFLEX-B-PA/2PET 20	20	30
FITCOFLEX-B-PA/2PET 25	25	36
FITCOFLEX-B-PA/2PET 30	30	49
FITCOFLEX-B-PA/2PET 40	40	64
FITCOFLEX-B-PA/2PET 50	50	75

*Other sizes on request

Packaging: On spools or cut lengths.